

INTOOL®



Набор концевых мер
1-100 мм, 112 шт.
сталь, класс точности 2
(DIN861)

| Номинальный размер (мм) | Идентификационный номер | Отклонение (μm) |
|-------------------------|-------------------------|------------------------------|
| 0.5 | 206162 | -0.10 |
| 1.0 | 208467 | -0.21 |
| 1.0005 | 205018 | -0.04 |
| 1.001 | 164738 | -0.10 |
| 1.002 | 201887 | +0.20 |
| 1.003 | 183422 | 0.00 |
| 1.004 | 205794 | -0.11 |
| 1.005 | 206805 | +0.20 |
| 1.006 | 201053 | -0.15 |
| 1.007 | 201920 | -0.15 |
| 1.008 | 197488 | -0.32 |
| 1.009 | 204144 | -0.15 |
| 1.01 | 200614 | -0.18 |
| 1.02 | 200143 | +0.25 |
| 1.03 | 204538 | +0.28 |
| 1.04 | 200465 | -0.20 |
| 1.05 | 191480 | -0.25 |
| 1.06 | 209165 | -0.19 |
| 1.07 | 205812 | +0.20 |
| 1.08 | 203121 | +0.25 |
| 1.09 | 201344 | -0.14 |
| 1.10 | 208751 | -0.15 |
| 1.11 | 202660 | -0.13 |
| 1.12 | 200878 | +0.20 |
| 1.13 | 198029 | -0.22 |
| 1.14 | 203597 | -0.08 |
| 1.15 | 193453 | +0.21 |
| 1.16 | 209046 | -0.17 |
| 1.17 | 193971 | -0.12 |
| 1.18 | 191252 | -0.20 |
| 1.19 | 203690 | -0.20 |
| 1.20 | 204143 | 0.00 |
| 1.21 | 201012 | -0.02 |
| 1.22 | 203587 | +0.09 |
| 1.23 | 201875 | -0.09 |
| 1.24 | 206434 | +0.05 |
| 1.25 | 208070 | -0.30 |
| 1.26 | 204132 | +0.20 |

| Номинальный размер (мм) | Идентификационный номер | Отклонение (μm) |
|-------------------------|-------------------------|------------------------------|
| 1.27 | 203083 | -0.10 |
| 1.28 | 192595 | -0.09 |
| 1.29 | 201197 | +0.06 |
| 1.30 | 198996 | -0.20 |
| 1.31 | 202524 | +0.30 |
| 1.32 | 190294 | 0.00 |
| 1.33 | 201247 | +0.22 |
| 1.34 | 204943 | -0.13 |
| 1.35 | 205516 | +0.20 |
| 1.36 | 194652 | +0.18 |
| 1.37 | 206108 | +0.25 |
| 1.38 | 209440 | -0.28 |
| 1.39 | 207949 | +0.24 |
| 1.40 | 206077 | +0.32 |
| 1.41 | 191361 | 0.00 |
| 1.42 | 196994 | -0.18 |
| 1.43 | 201088 | +0.18 |
| 1.44 | 202254 | +0.20 |
| 1.45 | 197652 | -0.11 |
| 1.46 | 203139 | -0.20 |
| 1.47 | 191377 | -0.20 |
| 1.48 | 200796 | +0.20 |
| 1.49 | 201874 | +0.23 |
| 1.50 | 204883 | -0.20 |
| 2 | 197780 | +0.35 |
| 2.5 | 202320 | +0.30 |
| 3 | 193820 | +0.28 |
| 3.5 | 196321 | -0.10 |
| 4 | 209228 | +0.29 |
| 4.5 | 199514 | -0.08 |
| 5 | 203895 | -0.10 |
| 5.5 | 206310 | -0.09 |
| 6 | 203855 | -0.10 |
| 6.5 | 198323 | -0.15 |
| 7 | 208243 | +0.20 |
| 7.5 | 191351 | +0.11 |
| 8 | 202283 | +0.25 |
| 8.5 | 207928 | -0.10 |

| Номинальный размер (мм) | Идентификационный номер | Отклонение (μ m) |
|-------------------------|-------------------------|------------------|
| 9 | 202636 | +0.26 |
| 9.5 | 205799 | -0.17 |
| 10 | 204276 | +0.20 |
| 10.5 | 205470 | -0.16 |
| 11 | 201807 | +0.35 |
| 11.5 | 201581 | +0.30 |
| 12 | 201869 | +0.11 |
| 12.5 | 195677 | +0.30 |
| 13 | 205835 | -0.18 |
| 13.5 | 201069 | -0.21 |
| 14 | 208224 | -0.26 |
| 14.5 | 203507 | -0.20 |
| 15 | 205614 | -0.08 |
| 15.5 | 200559 | -0.38 |
| 16 | 201021 | -0.25 |
| 16.5 | 200064 | +0.11 |
| 17 | 201569 | -0.28 |
| 17.5 | 201681 | +0.08 |
| 18 | 200948 | +0.40 |
| 18.5 | 183294 | 0.00 |
| 19 | 191337 | +0.39 |
| 19.5 | 203386 | +0.02 |
| 20 | 206501 | -0.20 |
| 20.5 | 204801 | -0.19 |
| 21 | 200385 | +0.25 |
| 21.5 | 201060 | +0.31 |
| 22 | 201315 | -0.02 |
| 22.5 | 201938 | -0.20 |
| 23 | 201767 | +0.30 |
| 23.5 | 203251 | -0.24 |
| 24 | 203182 | -0.38 |
| 24.5 | 196116 | +0.20 |
| 25 | 206096 | +0.30 |
| 50 | 208302 | +0.47 |
| 75 | 202487 | +0.04 |
| 100 | 206298 | -0.42 |

Примечание: Стандартная эталонная температура: 68°F (20°C)
Кoeffициент теплового расширения: $(11,5 \pm 1,0) \times 10^{-6}/^{\circ}\text{C}$